



COLOURS INCLUDE:

Available in 10 different shades, 4 with a co-ordinated face and back colour, Serene daylight is available from stock in the UK for next day delivery.



Serene Daylight dims the transmitted light creating a controlled and soothing environment in either the home or office.

Manufactured in Germany to the highest standards of quality and performance, the fabric is tested to satisfy the requirements of Oekotex 100, the European recognised certification guaranteeing total control of potentially harmful substances in manufacture, and no release of harmful VOCs to the environment.

Available in 10 different shades, 4 with a co-ordinated face and back colour, Serene daylight is available from stock in the UK for next day delivery.



Quality Management System ISO 9001:2008

Environmental Management System ISO 50001:2011

Energy Management System ISO 14001:2004



Technical data

Serene Daylight is available from stock in both roller , 89mm and 127mm vertical fabrics.

The fabric is stable to light, multi-directional, and a consistency of quality and performance, as befits one of Germany's most technically advanced fabric design manufacturers.

Technical Information

Useable for	Roller / Vertical / Panel tracks
Colour range	12
Fabric Composition	100% Polyester fabric
Fabric Width	230 cm / *300 cm
Fabric Weight	220 gsm
Fabric Thickness	0.3 mm
Moisture proofed	yes
PVC free	yes
Halogen free	yes
Antimony free	yes
Care	Wipe Clean
Flame retardant according to DIN 4102 B1, BS5867 part2 Type B	
Light Fastness	6-7

colour	Light Properties			Solar Properties			light fastness	UV Trans-mission	Gtot
	R	T	A	R	T	A			
1021 white*	72%	16%	12%	84%	15%	1%	6-7	0%	0,34
2025 beige*	64%	17%	19%	71%	15%	14%	6-7	1%	0,46
2272 sand*	64%	13%	23%	69%	9%	22%	6-7	0%	0,38
2103 vanilla*	70%	16%	14%	79%	14%	7%	6-7	0%	0,35
2071 cream	63%	15%	22%	70%	12%	18%	6-7	0%	0,51
4125 light green	60%	13%	27%	68%	9%	23%	6-7	0%	0,39
9124 light grey	62%	15%	23%	67%	11%	22%	6-7	0%	0,39
9037 mid grey*	52%	8%	40%	54%	9%	37%	6-7	0%	0,43
9001 dark grey*	32%	2%	66%	32%	2%	66%	6-7	0%	0,52
5049 blue	41%	6%	53%	31%	1%	68%	6-7	0%	0,38

R = Reflection, T = Transmission, A = Absorption
 UV Transmission: the percentage of UV light transmitted by the fabric
 Gtot: measure total solar energy that passes through the glazing system and the fabric



D black out



suitable for workstations



hand wash 30° C



Oeko-Tex Standard 100



Flame retardant according to DIN 4102 B1, BS5867 part2 Type B